

Product **1785-V30B** **PLC-5/30V Processor**
 1785-V40B **PLC-5/40V Processor**
 1785-V40L **PLC-5/40VL Processor**
 1785-V80V **PLC-5/80V Processor**

Battery

Catalog Number	1770-XYV									
Part Number	695603004 Lithium Battery Assembly 695603003 Lithium Battery									
Description	Lithium Contains 0.65 grams of lithium									
Supplier Part No	AESCO (Eagle Picher Keeper II LTC-3PN-S2 battery+ SAMTEC TS-104-G-C lead)									
Supplier Spec.	Lithium Thionyl Chloride 3.5v 350mAh Dimensions: .65 » lg x .25 » wi x .60 » dp (16.51mm x 6.35mm x 15.24mm) Weight: 4 grams									
Life	<table style="width: 100%; border: none;"> <tr> <td></td> <td style="text-align: center;">@ 60°C (140°F)</td> <td style="text-align: center;">@ 25°C (77°F)</td> </tr> <tr> <td>100 % power off</td> <td style="text-align: center;">40 days</td> <td style="text-align: center;">6 months</td> </tr> <tr> <td>50% power off</td> <td style="text-align: center;">125 days</td> <td style="text-align: center;">8 months</td> </tr> </table> <p>Battery low BATT LED indicates battery is low. The indicator first lights when the processor has 10 days of battery back-up power remaining.</p> <p>Shelf life = 6 to 6.5 years stored @ 70°F to 75°F</p>		@ 60°C (140°F)	@ 25°C (77°F)	100 % power off	40 days	6 months	50% power off	125 days	8 months
	@ 60°C (140°F)	@ 25°C (77°F)								
100 % power off	40 days	6 months								
50% power off	125 days	8 months								
Installation	1 behind processor front battery cover									
Accessories	Battery cover: Contact Product Services & Support PLC Group for replacement cover.									
Ref. Publication	1785-6.5.9 6/94 Pages 2-13, 2-14, C-2, D-1 PLC-5/VMEbus Programmable Controllers User Manual ICCG-5.14 Allen-Bradley Guidelines for Lithium Battery Handling and Disposal									
Notes										